

FIBRE CHANNEL

LOW COST 10km OPTICAL

1063 MBAUD INTERFACE

100-SM-LC-L

REV 2

working draft proposed
American National Standard
for Information Systems

February 11, 1998

Secretariat:
Information Technology Industry Council

ABSTRACT: This standard describes an enhancement to the ANSI X3.230, Fibre Channel Physical and Signalling Interface (FC-PH) and to the ANSI X3.297, Fibre Channel Physical and Signalling Interface - 2 (FC-PH-2) and to the ANSI X3.303, Fibre Channel Physical and Signalling interface - 3 (FC-PH-3) and is an addendum to these documents.

NOTE:

This is a draft proposed American National Standard of Accredited Standards Committee X3. As such, this is not a completed standard. The T11.2 Technical Committee may modify this document as a result of comments received during public review and its approval as a standard.

POINTS OF CONTACT:

Schelto VanDoorn (T11.2 Chairman)
Siemens Components, Inc.
19000 Homestead Road
Cupertino, CA 95014
(408)725-3436 Fax: (408)725-3435
E-Mail: schelto.van-doorn@sci.siemens.com

Edward L. Grivna (T11.2 Vice Chairman)
Cypress Semiconductor
2401 East 86th Street
Bloomington, MN 55425
(612) 851-5046 Fax: (612) 851-5087
E-Mail: elg@cypress.com

Steve Joiner (T11.2 Optics Working Group Chairman)
Hewlett Packard
350 West Trimble Road
San Jose, CA 95131
(408)435-6421 Fax: (408)435-6286
E-mail: steve_joiner@hp.com

James E. Myers (Editor)
IBM Corporation
3605 Highway 52N
Rochester, MN 55901
(507) 253-0370 Fax: (507) 253-1438
E-Mail: james_myers@vnet.ibm.com

American National Standard
for Information Technology —
Fibre Channel—
Low Cost 10km Optical 1063MBaud Interface
(100-SM-LC-L)

Secretariat

Information Technology Industry Council

Approved ,199

American National Standards Institute, Inc.

Abstract

This standard describes the enhancement to the ANSI X3.230, Fibre Channel Physical and Signalling Interface (FC-PH), to the ANSI X3.297, Fibre Channel Physical and Signalling Interface - 2 (FC-PH-2) and to the ANSI X3.xxx, Fibre Channel Physical and Signaling Interface - 3 (FC-PH-3), and is an addendum to these documents.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made towards their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give interpretation on any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

**American National Standards Institute
11 W. 42nd Street, New York, New York 10036**

Copyright © 199x by American National Standards Institute
All rights reserved

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

INSERT CODE HERE

Contents

	Page
Foreword	vi
1 Scope	1
2 Normative References	1
2.1 Approved references	1
3 Definitions and conventions	1
3.1 Definitions	1
4 Structure and concepts	1
5 FC-0 functional characteristics	1
5.1 General Characteristics	1
5.2 FC-0 nomenclature	2
5.3 FC-0 technology options	2
6 Optical fibre interface specification	2
6.1 SM data links	2
6.1.3 SM optical response specifications	3
6.1.4 100-SM-LC-L transmitter specifications	4
6.1.5 100-SM-LC-L jitter specifications	4
6.1.5.1 100-SM-LC-L jitter budget table	4
6.1.5.2 Receiver output jitter measurement	4
7 Electrical cable plant specification	5
8 Optical fibre cable plant specification	5
8.1 SM cable plant specification	5
8.2 Cable plant loss budget	6

Tables

Table 1 – Optical Media Signal Interface Overview	2
Table 2 – Optical Cable Plant Overview	2
Table 3 – FC-0 physical links for single-mode classes	3
Table 4 – 100-SM-LC-L jitter budget	4
Table 5 – Single-mode cable plant	5

Figures

Figure 1 – FC-0 nomenclature	2
Figure 2 – 100-SM-LC-L transmitter specifications	4

Foreword (This Foreword is not part of dpANS X3.xxx-199x.)

This Fibre Channel, Low Cost 10km Optical 1063 Mbaud Interface standard (100-SM-LC-L) describes an enhancement to the ANSI X3.230-1994 (FC-PH), X3.297-1997 (FC-PH-2), and X3.303-199X (FC-PH-3) and is an extension to these documents.

This standard was developed by Task Group T11.2 of Accredited Standards Committee NCITS during 1997-8. The standards approval process started in 1997.

Requests for interpretation, suggestions for improvement or addenda, or defect reports are welcome. They should be sent to the National Committee for Information Technology (NCITS), 1250 Eye Street, NW, Suite 200, Washington, DC 20005.

NOTE: The developers of this standard have requested that holders of patents that may be required for the implementation of the standard, disclose such patents to the publisher. However neither the developers nor the publisher have undertaken a patent search in order to identify which if any patents may apply to this standard. No position is taken with respect to the validity of any claim or any patent rights that may have been disclosed. Details may be obtained from the publisher concerning any statement of patents and willingness to grant a license on a nondiscriminatory basis and with reasonable terms and conditions to applicants desiring to obtain such a license.

This standard was processed and approved for submittal to ANSI by NCITS. Committee approval of the standard does not necessarily imply that all committee members voted for approval. At the time it approved this standard, NCITS had the following members:

TBD, Chair
TBD, Vice-Chair
TBD, Secretary

Organization Represented Name of Representative

TBDTBD
TBD

Technical Committee T11.2 on Device Level Interfaces, which developed this standard, had the following participants:

Schelto VanDorn, Chair
Edward Grivna, Vice-Chair
James Myers, 100-SM-LC-L Technical Editor

List of Committee Members

Organization	Name of Representative
3M	Tad Szostak Michael E. Griffin Ron Brossard
Alcoa-Fujikura	Ronald J. Kleckowski Kennedy X. Vines
AMP	Charles Brill Dan Brown
Amphenol Int.....	Bill Mable
Berg Electronics.....	Daniel Casey
Cypress.....	Edward L. Grivna
DEC	Bill Ham David Hyer
DPT	Roger Cummings
Emulex	Hassein Hashemi
Framatome.....	J. J. Dumont
Fujikura America	Hari Naidu Robert Dahlgren Chris Simoneaux
G2 Networks	Rich Taborek Trevor Pearman Mike Breneman
Gadzoos.....	Howey Chin Alistair Black William R. Martin
Gore	Christine Foster Mark Donhowe
Hirose	Karl Kwiat Tatsua Arai
Honeywell	Jim Tatum Bill Marsh
HP	Steve Joiner Robert Mejia
IBM.....	Ron Soderstrom James Myers Jonathan Thatcher
Interphase	David Lawson Ravi Anantharaman
JPM	Rick Hardy
LSI Logic.....	Michael Jenkins Karl Nakamura
Lucent Technologies.....	Louise Bryant
Method	Vince Melendy Luis Torres
Mitre	Virginia F. Haydu James R. Johns
Motorola	Daniel Schwartz
Network Systems STK	Ed Fiore
NCR	Dennis Russell Ted DiBenel
Seagate.....	Allen N. Kramer
SGS-Thomson	Colin Whitby-Stevens
Siecor	Todd Hudson
Siemens	Schelto Van Doorn Stephan Meyer
Sumitomo Electric	Paul Pace
Sun Microsystems.....	Ali Ghiasi Robert N. Snively
Symbios Logic.....	Scott R. Bruns David Allen John Lohmeyer
Technitrol	Richard Schwarz Keith Conroy
TI.....	David K. Johnson

List of Committee Members

Organization	Name of Representative
Unisys	Edward Chang
	Arlan Stone
Vitesse	Bob Rumer
	John Schaefer
Vixel	Tom Lindsay
	Mike Dudek
VLSI Technology.....	Ryuji Yonemoto
	Regi Thomas
Western Digital.....	Jeffrey L. Williams
	Gregory Kapraun
Xyratex	David E. Instone
	Paul A. Levin

draft proposed American National Standard
for Information Technology—

Fibre Channel — Low Cost 10km Optical 1063MBaud Interface — (100-SM-LC-L)

1 Scope

100-SM-LC-L describes an enhancement to ANSI X3.230, FC-PH, to ANSI X3.297, FC-PH-2 and to ANSI X3.303, FC-PH-3, and is an addendum to the FC-PH, FC-PH-2, and FC-PH-3 documents.

This document is an extension to the FC-PH, FC-PH-2, and FC-PH-3 standards and describes a low cost 10km optical interface.

2 Normative References

The following standards contain provisions which, through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below.

Copies of the following documents can be obtained from ANSI: Approved ANSI standards, approved and draft international and regional standards (ISO, IEC, CEN/CENELEC, ITUT), and approved foreign standards (including BSI, JIS, and DIN). For further information, contact ANSI Customer Service Department at 212-642-4900 (phone), 212-302-1286 (fax) or via the World Wide Web at <http://www.ansi.org>.

2.1 Approved references

ANSI X3.230-1994, *Fibre Channel Physical and Signalling Interface (FC-PH)*

ANSI X3.297-1996, *Fibre Channel Physical and Signalling Interface - 2(FC-PH-2)*

ANSI X3.303-199X, *Fibre Channel Physical and Signalling Interface - 3(FC-PH-3)*

3 Definitions and conventions

For 100-SM-LC-L, the following definitions and the definitions, conventions, abbreviations, acronyms, and symbols defined in X3.230-1994 (FC-PH), X3.297-1996 (FC-PH-2), and X3.303-199X (FC-PH-3) apply.

3.1 Definitions

3.1.1 $T_{RISE\FALL}$: The adjusted 20% to 80% rise and/or fall times of the optical signal.

3.1.2 $T_{RISE\FALL_MEASURED}$: The measured 20% to 80% rise and/or fall times of the optical signal.

3.1.3 $T_{RISE\FALL_FILTER}$: The measured 20% to 80% rise and/or fall times of a fourth order Bessel Thompson filter

4 Structure and concepts

No change.

5 FC-0 functional characteristics

The enhancement of an additional physical variant to FC-PH, FC-PH-2, and FC-PH-3, is specified.

5.1 General characteristics

The FC-2 protocol is defined to operate across connections having a BER detected at the receiving node of 10^{-12} . It shall be the combined responsibility of the component vendors and the system integrator to ensure that this level of service is provided in a given Fibre Channel installation.

The general characteristics specified in FC-PH 5.1 are enhanced as follows:

— A low cost 10km interface operating at a data rate of 1 063 MBaud using a long wave-length (1310nm) laser on single mode fiber is defined in this standard.

5.2 FC-0 nomenclature

The nomenclature for the technology options are illustrated in Figure 1.

5.3 FC-0 technology options

Optical media signal interface enhancements are included in table 1 based on FC-PH table 2.

Optical cable plant enhancements are included in table 2 based on FC-PH table 4.

Table 1 – Optical Media Signal Interface Overview

100 MB/sec 1,062 Gbaud
100-SM-LC-L Subclause 6.1 SM 1310nm 2m-10km

Table 2 – Optical Cable Plant Overview

Single Mode
100-SM-LC-L Subclause 6.1 SM 1310nm 2m-10km




Figure 1 – FC-0 nomenclature

6 Optical fibre interface specification

Enhancement to FC-PH, FC-PH-2, and FC-PH-3 is specified.

6.1 SM data links

Table 3 includes a low cost 10km link operating at 1063 MBaud using a long wave wavelength (1310nm) laser on single mode fiber. The optical power coupled into the fibre shall be limited to a maximum value consistent with Class 1 laser safety operations in accordance with IEC 825-1.

Table 3 – FC-0 physical links for single-mode classes

FC-0	Units	100-SM-LC-L
Subclause		FC-PH-2 6.1
Data rate	MB/sec	100
Nominal bit rate	MBaud	1062.5
Tolerance	ppm	±100
Operating range	m	2-10k
Fibre core diameter	µm	9
Transmitter (S)		
Type		Laser
λ (Spectral centre wavelength)	nm (min.)	(C)
	nm (max.)	(C)
RMS spectral width	nm (max.)	(C)
Launched power, max.	dBm (ave.)	-3
Launched power, min.	dBm (ave.)	(C)
Extinction ratio	dB (min.)	9
RIN (max.)	dB/Hz	-116
Rise and fall time (A)	ps (max) (20%-80%)	320
Eye opening (B)	% (min.)	57
Deterministic jitter	% (p-p)	20
Receiver (R)		
Received power, min. (D)	dBm (ave.)	-20
Received power, max.	dBm (ave.)	-3
Optical path penalty	dB (max.)	4.2
Return loss of receiver	dB (min.)	12
(A) See subclause 6.1.3 (B) @BER≤10 ⁻¹² (C) Trade-offs are available between spectral centre wavelength, RMS spectral width, and minimum launched power. See subclause 6.1.4 and Figure 2. (D) Receiver sensitivity is measured by sampling at the center of the eye while using a minimum specified extinction ratio source.		

6.1.3 SM optical response specifications

Optical response time specifications are based on the unfiltered waveforms. For the purposes of standardizing the measurement method, measured waveforms shall conform to the mask defined in FC-PH Figure 22: **Transmitter eye diagram mask**. If a filter is needed to conform to the mask, the filter response effect should be removed from the measured rise and fall times using the equation:

$$T_{RISE\FALL} = \sqrt{(T_{RISE\FALL_MEASURED}^2) - (T_{RISE\FALL_FILTER}^2)}$$

The optical signal may have different rise and fall times. Any filter should have an impulse response equivalent to a fourth order Bessel Thompson filter.

6.1.4 100-SM-LC-L transmitter specifications

Figure 2 shows the relative trade-offs in transmitter specifications. Choosing a minimum launched power defines a compliance curve. Transmitter specifications for maximum spectral width and minimum and maximum spectral center wavelength are then defined acceptably as any point on or below the corresponding minimum launched power curve.




Figure 2 – 100-SM-LC-L transmitter specifications

6.1.5 100-SM-LC-L jitter specifications

6.1.5.1 100-SM-LC-L jitter budget table

The numbers in Table 4 represent high frequency jitter (above 637 kHz) and do not include low frequency jitter or wander.

Table 4 – 100-SM-LC-L jitter budget

Compliance point	Total jitter		Deterministic jitter		Reference
	UI	ps	UI	ps	
b (Serial Output) α_T	0.210	198	0.100	94	Compliance points are defined in FC-PH Figure 9: FC-0 transmitter interfaces , and in FC-PH Figure 10: FC-0 receiver interfaces ; and in Fibre Channel Methodologies for Jitter Specification Technical Report
S (Media Output) γ_T	0.430	405	0.200	188	
R (Media Input) γ_R	0.430	405	0.200	188	
c (Receiver Output) α_R	0.600	565	0.380	358	

6.1.5.2 Receiver output jitter measurement

Receiver TJ and DJ must comply to the listed values in Table 4 over all allowable optical power input ranges and extinction ratios as listed in Table 3. The minimum optical power input test condition may need to be adjusted to account for penalties inherent in the test setup. (Eg. a 0.6 dB reflection degradation in the test setup would require a minimum optical power input of -19.4 dBm)

7 Electrical cable interface specification

No changes.

8 Optical fibre cable plant specification

Enhancement to FC-PH, FC-PH-2, and FC-PH-3 is specified.

8.1 SM cable plant specification

This subclause specifies a single-mode cable plant (see FC-PH 3.1.17 for definition) for the Low Cost 10km Optical 1063 MBaud Interface (100-SM-LC-L).

Table 5 – Single-mode cable plant

FC-0	Unit	100-SM-LC-L
Subclause		6.1
Operating range	m	2-10k
Cable plant dispersion	ps/nm	35
Dispersion related penalty (-9.5 dBm minimum launched power)	dB	1.7
Dispersion related penalty (-9.0 dBm minimum launched power)	dB	2.2
Dispersion related penalty (-8.5 dBm minimum launched power)	dB	2.7
Dispersion related penalty (-8.0 dBm minimum launched power)	dB	3.2
Reflection related penalty	dB	1.0
Loss budget	dB	7.8

8.2 Cable plant loss budget

The passive loss budget for the 100-SM-LC-L shall be no greater than specified in table 5. This limit was arrived at by taking the difference between the minimum transmitter output power (from clause 6.1, figure 2), and the receiver sensitivity (from clause 6.1, table 3) and subtracting a 1dB reflection link penalty and a dispersion penalty corresponding to the minimum transmitter output power.

The dispersion related penalties shown in table 5 are the maximum calculated dispersion related penalties based on the corresponding transmitter specification curve as shown in clause 6.1.4, figure 2.

No changes to all remaining clauses of FC-PH.